



MIM

Marine- und Industrie-Montage GmbH

MecLev size	Bolt size	Tightening torque	Bolt size	Tightening torque	Bolt size	Tightening torque	Minimal height	Nominal height	Maximum height	Minimum reduced height	Maximum extended height	Bolt hole	Outside diameter	Key holes	Pitch	Rated load	Weight
-	M	Nm	M	Nm	M	Nm	mm	mm	mm	mm	mm	mm	mm	mm	mm	kN	Kg
ML-1216	12	81	14	129	16	200	30,0	34,0	38,0	23	55	17	55	5	2	120	0,5
ML-1620	16	200	18	287	20	405	35,0	41,5	48,0	23	75	21	75	6	2	165	1,1
ML-2024	20	405	22	556	24	698	40,0	46,5	53,0	28	95	25	95	8	2	245	2
ML-2430	24	698	27	1033	30	1402	45,0	53,0	61,0	30	115	31	115	8	2	320	3,3
ML-3036	30	1402	33	1898	36	2439	50,0	58,0	66,0	35	130	37	130	8	2	500	4,6
ML-3642	36	2439	39	3159	42	3904	55,0	63,0	71,0	40	150	44	150	8	2	700	6,7
ML-4248	42	3904	45	4876	48	5897	60,0	68,0	76,0	45	180	50	180	10	2	955	10,5
ML-4856	48	5897	52	7579	56	9454	70,0	79,0	88,0	53	210	60	210	10	3	1265	16,8
ML-5664	56	9454	60	11729	64	14119	75,0	84,0	93,0	58	220	66	220	10	3	1490	19,6
ML-6472	64	14119	68	*	72	*	80,0	89,0	98,0	63	240	74	240	10	3	1840	27,5

