SAFETY DATA SHEET

1. Identification

Product identifier Chockfast Blue Resin

Other means of identification

SKU# GP106R

Recommended use Not available.

Recommended restrictions None known.

Manufacturer/Importer/Supplier/Distributor information

Manufacturer

Company name ITW Engineered Polymers
Address 130 Commerce Drive
Montgomeryville, PA 18936

United States

Telephone Customer Service 215-855-8450

Website www.itwengineeredpolymers.com

E-mail orders.na@itwep.com
Contact person EHS Department

Emergency phone number CHEMTREC 800-424-9300

International 703-527-3887

2. Hazard(s) identification

Physical hazards Not classified.

Health hazards Skin corrosion/irritation Category 2

Serious eye damage/eye irritation Category 2
Sensitization, skin Category 1
Hazardous to the aquatic environment, Category 3

Environmental hazards Hazardous to the aquatic environment,

long-term hazard

OSHA defined hazards Not classified.

Label elements



Signal word Warning

Hazard statement Causes skin irritation. May cause an allergic skin reaction. Causes serious eye irritation. Harmful

to aquatic life with long lasting effects.

Precautionary statement

Prevention Avoid breathing mist or vapor. Wash thoroughly after handling. Contaminated work clothing must

not be allowed out of the workplace. Avoid release to the environment. Wear eye protection/face

protection. Wear protective gloves.

Response If on skin: Wash with plenty of water. If in eyes: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing. If skin irritation or rash occurs: Get medical advice/attention. If eye irritation persists: Get medical advice/attention. Take

off contaminated clothing and wash before reuse.

Storage Store away from incompatible materials.

Disposal Dispose of contents/container in accordance with local/regional/national/international regulations.

Hazard(s) not otherwise

classified (HNOC)

None known.

GP106R Version #: 03 Revision date: 04-25-2017 Issue date: 02-09-2014

98.8% of the mixture consists of component(s) of unknown acute oral toxicity. 98.8% of the mixture consists of component(s) of unknown acute dermal toxicity. % of the mixture consists of component(s) of unknown acute inhalation toxicity. 98.8% of the mixture consists of component(s) of unknown acute hazards to the aquatic environment. 84.04% of the mixture consists of component(s) of unknown long-term hazards to the aquatic environment.

3. Composition/information on ingredients

Mixtures

Chemical name	Common name and synonyms	CAS number	%
Crystalline SiO2 (Quartz)		14808-60-7	60 - 100
Epoxy Resin:reaction Product Of Bisphenol A And Epichlorohydrin (refer To Epichlorohydrin)		25068-38-6	10 - 30
Cyclic ester		14228-73-0	1 - 5
Other components below reportable	levels		7 - 15

^{*}Designates that a specific chemical identity and/or percentage of composition has been withheld as a trade secret.

4. First-aid measures

Inhalation Move to fresh air. Call a physician if symptoms develop or persist.

Remove contaminated clothing immediately and wash skin with soap and water. In case of Skin contact

eczema or other skin disorders: Seek medical attention and take along these instructions. Wash

contaminated clothing before reuse.

Eye contact Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion Rinse mouth. Get medical attention if symptoms occur.

Symptoms may be delayed.

Most important

symptoms/effects, acute and

delayed

Provide general supportive measures and treat symptomatically. Keep victim under observation.

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis.

Indication of immediate medical attention and special treatment needed

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to

protect themselves. Wash contaminated clothing before reuse.

5. Fire-fighting measures

Suitable extinguishing media

Unsuitable extinguishing media

Water fog. Foam. Dry chemical powder. Carbon dioxide (CO2).

Do not use water jet as an extinguisher, as this will spread the fire.

Specific hazards arising from

the chemical

During fire, gases hazardous to health may be formed.

Special protective equipment and precautions for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Fire fighting

equipment/instructions

Move containers from fire area if you can do so without risk.

Specific methods General fire hazards Use standard firefighting procedures and consider the hazards of other involved materials.

No unusual fire or explosion hazards noted.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Keep unnecessary personnel away. Keep people away from and upwind of spill/leak. Wear appropriate protective equipment and clothing during clean-up. Avoid breathing mist or vapor. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing. Ensure adequate ventilation. Local authorities should be advised if significant spillages cannot be contained. For personal protection, see section 8 of the SDS.

Material name: Chockfast Blue Resin

Methods and materials for containment and cleaning up

Prevent entry into waterways, sewer, basements or confined areas.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb in vermiculite, dry sand or earth and place into containers. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills to original containers for re-use. For waste disposal, see section 13 of the SDS.

Environmental precautions

Avoid release to the environment. Inform appropriate managerial or supervisory personnel of all environmental releases. Prevent further leakage or spillage if safe to do so. Avoid discharge into drains, water courses or onto the ground.

7. Handling and storage

Precautions for safe handling

Avoid breathing mist or vapor. Avoid contact with eyes, skin, and clothing. Avoid prolonged exposure. Provide adequate ventilation. Wear appropriate personal protective equipment. Avoid release to the environment. Observe good industrial hygiene practices.

Conditions for safe storage, including any incompatibilities

Store in original tightly closed container. Store away from incompatible materials (see Section 10 of the SDS).

8. Exposure controls/personal protection

Occupational exposure limits

The following constituents are the only constituents of the product which have a PEL. TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Components	Туре	Value	
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	PEL	0.05 mg/m3	
US. OSHA Table Z-3 (29 CFR 1910	.1000)		
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.1 mg/m3	Respirable.
,		2.4 mppcf	Respirable.
US. ACGIH Threshold Limit Values	S		
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.025 mg/m3	Respirable fraction.
US. NIOSH: Pocket Guide to Chem	nical Hazards		
Components	Туре	Value	Form
Crystalline SiO2 (Quartz) (CAS 14808-60-7)	TWA	0.05 mg/m3	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Appropriate engineering controls

Good general ventilation (typically 10 air changes per hour) should be used. Ventilation rates should be matched to conditions. If applicable, use process enclosures, local exhaust ventilation, or other engineering controls to maintain airborne levels below recommended exposure limits. If exposure limits have not been established, maintain airborne levels to an acceptable level. Provide eyewash station. Eye wash fountain and emergency showers are recommended.

Individual protection measures, such as personal protective equipment

Face shield is recommended. Wear safety glasses with side shields (or goggles). Eye/face protection

Skin protection

Hand protection Wear appropriate chemical resistant gloves.

Other Wear appropriate chemical resistant clothing. Use of an impervious apron is recommended.

Respiratory protection In case of insufficient ventilation, wear suitable respiratory equipment.

Thermal hazards Wear appropriate thermal protective clothing, when necessary.

General hygiene considerations

Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants. Contaminated work clothing should not be allowed out of the workplace.

GP106R Version #: 03 Revision date: 04-25-2017 Issue date: 02-09-2014

9. Physical and chemical properties

Appearance Viscous. Liquid.

Physical state Liquid.
Form Liquid.
Color Blue
Odor Slight.

Odor thresholdNot available.pHNot available.Melting point/freezing pointNot available.

Initial boiling point and boiling

> 500 °F (> 260 °C)

range

Flash point > 400.0 °F (> 204.4 °C) Pensky-Martens Closed Cup

Evaporation rate Not available.

Flammability (solid, gas) Not applicable.

Upper/lower flammability or explosive limits

Flammability limit - lower

Not available.

(%)

Flammability limit - upper

Not available.

(%)

Explosive limit - lower (%) Not available.

Explosive limit - upper (%) Not available.

Vapor pressure 0.03 mm Hg

Vapor density > 1

Relative density Not available.

Solubility(ies)

Solubility (water) Not available.

Partition coefficient Not available.

(n-octanol/water)

Auto-ignition temperatureNot available.Decomposition temperatureNot available.ViscosityNot available.

Other information

Density2.17 g/cm3Explosive propertiesNot explosive.Oxidizing propertiesNot oxidizing.

Specific gravity 2.17

10. Stability and reactivity

ReactivityThe product is stable and non-reactive under normal conditions of use, storage and transport.

Chemical stability Material is stable under normal conditions.

Possibility of hazardous

reactions

No dangerous reaction known under conditions of normal use.

Conditions to avoid Contact with incompatible materials.

Incompatible materials Strong oxidizing agents.

Hazardous decomposition

products

No hazardous decomposition products are known.

11. Toxicological information

Information on likely routes of exposure

Inhalation Prolonged inhalation may be harmful.

Skin contact Causes skin irritation. May cause an allergic skin reaction.

Eye contact Causes serious eye irritation.

Material name: Chockfast Blue Resin

Ingestion Expected to be a low ingestion hazard.

Symptoms related to the physical, chemical and

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction.

Dermatitis. Rash. toxicological characteristics

Information on toxicological effects

Acute toxicity Not known.

Skin corrosion/irritation Causes skin irritation.

Serious eye damage/eye

irritation

Causes serious eye irritation.

Respiratory or skin sensitization

Respiratory sensitization Not a respiratory sensitizer.

Skin sensitization May cause an allergic skin reaction.

No data available to indicate product or any components present at greater than 0.1% are Germ cell mutagenicity

mutagenic or genotoxic.

Carcinogenicity Not classifiable as to carcinogenicity to humans.

IARC Monographs. Overall Evaluation of Carcinogenicity

Crystalline SiO2 (Quartz) (CAS 14808-60-7) 1 Carcinogenic to humans.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

US. National Toxicology Program (NTP) Report on Carcinogens

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Known To Be Human Carcinogen.

This product is not expected to cause reproductive or developmental effects. Reproductive toxicity

Specific target organ toxicity -

single exposure

Not classified.

Specific target organ toxicity -

repeated exposure

Not classified.

Not an aspiration hazard. **Aspiration hazard**

Chronic effects Prolonged inhalation may be harmful.

12. Ecological information

Ecotoxicity Harmful to aquatic life with long lasting effects.

Persistence and degradability Bioaccumulative potential

Mobility in soil No data available.

Other adverse effects No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation

potential, endocrine disruption, global warming potential) are expected from this component.

13. Disposal considerations

Disposal instructions Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Do not allow

this material to drain into sewers/water supplies. Do not contaminate ponds, waterways or ditches

with chemical or used container. Dispose of contents/container in accordance with

local/regional/national/international regulations.

Local disposal regulations Dispose in accordance with all applicable regulations.

Hazardous waste code The waste code should be assigned in discussion between the user, the producer and the waste

disposal company.

Waste from residues / unused

products

Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see:

Disposal instructions).

Contaminated packaging Since emptied containers may retain product residue, follow label warnings even after container is

emptied. Empty containers should be taken to an approved waste handling site for recycling or

disposal.

14. Transport information

DOT

Not regulated as dangerous goods.

IATA

UN number UN3082

Material name: Chockfast Blue Resin GP106R Version #: 03 Revision date: 04-25-2017 Issue date: 02-09-2014 UN proper shipping name Environmentally hazardous substance, liquid, n.o.s. (Bisphenol A/ Epichlorohydrin Resin)

Transport hazard class(es)

9 Class Subsidiary risk Ш Packing group **Environmental hazards** Yes **ERG Code** 9L

Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Other information

Allowed with restrictions. Passenger and cargo

aircraft

Cargo aircraft only Allowed with restrictions.

IMDG

UN3082 **UN number**

UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (Bisphenol A/

Epichlorohydrin Resin), MARINE POLLUTANT (Epoxy Resin)

Transport hazard class(es)

Class 9 Subsidiary risk Packing group Ш **Environmental hazards**

Marine pollutant Yes F-A. S-F **EmS**


Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

Epoxy Resin

Transport in bulk according to Annex II of MARPOL 73/78 and Not established.

the IBC Code

IATA; IMDG



Marine pollutant



General information IMDG Regulated Marine Pollutant.

15. Regulatory information

US federal regulations This product is a "Hazardous Chemical" as defined by the OSHA Hazard Communication

Standard, 29 CFR 1910.1200.

TSCA Section 12(b) Export Notification (40 CFR 707, Subpt. D)

Not regulated.

CERCLA Hazardous Substance List (40 CFR 302.4)

Not listed.

SARA 304 Emergency release notification

Not regulated.

OSHA Specifically Regulated Substances (29 CFR 1910.1001-1050)

Not regulated.

Superfund Amendments and Reauthorization Act of 1986 (SARA)

Hazard categories Immediate Hazard - Yes

Delayed Hazard - No Fire Hazard - No Pressure Hazard - No Reactivity Hazard - No

SARA 302 Extremely hazardous substance

Not listed.

SARA 311/312 Hazardous No

chemical

SARA 313 (TRI reporting)

Not regulated.

Other federal regulations

Clean Air Act (CAA) Section 112 Hazardous Air Pollutants (HAPs) List

Not regulated.

Clean Air Act (CAA) Section 112(r) Accidental Release Prevention (40 CFR 68.130)

Not regulated.

Safe Drinking Water Act

(SDWA)

Not regulated.

US state regulationsCalifornia Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65): This material

is not known to contain any chemicals currently listed as carcinogens or reproductive toxins.

US - California Proposition 65 - CRT: Listed date/Carcinogenic substance

Crystalline SiO2 (Quartz) (CAS 14808-60-7) Listed: October 1, 1988

US. California. Candidate Chemicals List. Safer Consumer Products Regulations (Cal. Code Regs, tit. 22, 69502.3, subd. (a))

Crystalline SiO2 (Quartz) (CAS 14808-60-7)

International Inventories

Country(s) or region	Inventory name	On inventory (yes/no)*
Australia	Australian Inventory of Chemical Substances (AICS)	Yes
Canada	Domestic Substances List (DSL)	Yes
Canada	Non-Domestic Substances List (NDSL)	No
China	Inventory of Existing Chemical Substances in China (IECSC)	Yes
Europe	European Inventory of Existing Commercial Chemical Substances (EINECS)	No
Europe	European List of Notified Chemical Substances (ELINCS)	No
Japan	Inventory of Existing and New Chemical Substances (ENCS)	No
Korea	Existing Chemicals List (ECL)	Yes
New Zealand	New Zealand Inventory	Yes
Philippines	Philippine Inventory of Chemicals and Chemical Substances (PICCS)	Yes

^{*}A "Yes" indicates that all components of this product comply with the inventory requirements administered by the governing country(s)

Toxic Substances Control Act (TSCA) Inventory

16. Other information, including date of preparation or last revision

 Issue date
 02-09-2014

 Revision date
 04-25-2017

Version # 03
HMIS® ratings Health: 2

Flammability: 0 Physical hazard: 1

Material name: Chockfast Blue Resin

United States & Puerto Rico

SDS US

GP106R Version #: 03 Revision date: 04-25-2017 Issue date: 02-09-2014

Yes

A "No" indicates that one or more components of the product are not listed or exempt from listing on the inventory administered by the governing country(s).

NFPA ratings Health: 2

Flammability: 1
Instability: 1

Disclaimer ITW Engineered Polymers cannot anticipate all conditions under which this information and its

product, or the products of other manufacturers in combination with its product, may be used. It is the user's responsibility to ensure safe conditions for handling, storage and disposal of the product, and to assume liability for loss, injury, damage or expense due to improper use. The information in the sheet was written based on the best knowledge and experience currently

available.

Revision informationThis document has undergone significant changes and should be reviewed in its entirety.

Material name: Chockfast Blue Resin